

RHE20 SI ER HPR

Technical data according to EN 410 and EN 673

4 mm single

4 / 16 / 4 mm double

Corrected emissivity of uncoated glass surface

0.837

Solar Energy Transmission, τ_e	10 %	9 %
Solar Energy Reflection, ρ_e	62 %	62 %
Solar Energy Absorption, a_e	28 %	29 %

Visible Light Transmission, τ_V	14 %	13 %
Visible Light Reflection (External) , ρ_{Ve}	65 %	65 %
Visible Light Reflection (Internal) , ρ_{Vi}	61 %	59 %

Ultraviolet Transmission, τ_{UV}	< 1 %
Ultraviolet Rejection	> 99 %

g value	0.17	0.13
Shading Coefficient	0.20	0.17
Total Solar Energy Rejected	83 %	87 %
Glare Reduction	85 %	86 %

U value, single glazing (W/m ² .K)	5.7	-
U value, double glazing, Air filled (W/m ² .K)	-	2.8

Emissivity, ϵ_n	0.87
--------------------------	------

Thickness without liner	60 μ
-------------------------	----------

Film Colour / Appearance	Silver
Installation position	Exterior
Warranty	7 years vertical / 5 years sloping (slopes 20 degrees or more from horizontal)**

Installation Notes: Edge sealing required. Use Film On for installation.

* Please check the complete Film to Glass Thermal Stress Compatibility Guidelines **before** film installation. ** Contact Solutia Performance Films for full details. All values for engineering parameters are determined by the manufacturer and independent testing laboratories.

RHE20 SI ER HPR

Features & Benefits

- The optimal solution for buildings which have to deal with high solar heat gain and therefore high cooling costs
- Reflective solar control and privacy exterior grade film
- Special technology polymeric scratch resistant coating provides increased durability and easier cleaning – patent applied for
- Significant improvement of working conditions – high reduction in solar heat gain
- Reduction in air-conditioning costs and hence a reduction in energy costs with potential payback of less than 3 years.
- Potential to reduce CO2 emissions by tens of tonnes per year
- Daylight privacy – ‘one way’ mirror effect can be achieved under the correct lighting conditions
- Excellent glare reduction for reduced eyestrain and easier working with computer screens
- Excellent UV filtering integral to the polyester – helps to reduce fading of textiles, furniture, and works of art
- Extremely well adapted to single, double and double low-E insulating glazing systems
- Exterior installation

RHE20 SI ER HPR Spectra

